

**HINO**

**XL | SERIES**





# THE LEGENDARY TURBO DIESEL

With a proven track record, the state-of-the-art Hino A09 Turbo Diesel engine powers the new Hino XL Series. Renowned globally for driving performance, economy, durability, and reliability. Nothing has been left to chance. That's the Hino way.



## HINO A09 SPECIFICATIONS


Configuration	Inline 6 Cylinder	
Displacement	8.9 L (541 cu in)	
Compression Ratio	17:1	
Bore	112 mm (4.4 in)	
Stroke	150 mm (5.9 in)	
Dry Weight	884 kg (1949 lb)	
Oil Capacity	34 L (36 qt)	
B10 Life Rating	1,600,000 KMS	
Horsepower	300 HP	360 HP
Torque	900 lb-ft	1150 lb-ft

# INSPIRING AND STRONG!



#### **COLLISION MITIGATION SYSTEM**

Available radar-based collision mitigation system provides active braking on moving and stationary vehicles – in all visibility conditions.



#### **ELECTRONIC STABILITY CONTROL**

Automatically intervenes when there is a high risk of directional instability that could lead to loss of vehicle control or rollover. Standard on all Tractors.



#### **LANE DEPARTURE WARNING**

An available camera-based system that helps reduce road run-offs, side swipes, and head-on collisions due to driver inattention or fatigue through distinct audible warnings for unintentional lane departures.

# **[ACTIVE] SAFETY FIRST.**

Safety starts before you turn on the engine. The Hino XL Series cab has been designed for safe, easy entry and exit with exterior grab handles, deep all-weather grip steps and extra wide door openings. Standard LED headlights, a high seating position and a 2,385 sq. in. windshield provide maximum visibility for the driver. Advanced active safety systems are also available on all models.

**HINO**  
**XL | SERIES**



# COMFORT. PERFORMANCE.

Distinguished by its rich design and automotive grade quality finish, the Hino XL Series interior is easy on the eyes [styling and ergonomically] and your back. The standard air-ride cab and driver's seat put layers of air between you and the rough road. Included premium features like hands-free Bluetooth audio/calling with steering wheel controls, a large LCD information center display, cruise control, and air conditioning enhance operator effectiveness.

## HINO XL | SERIES

## VERSATILITY FOR YOUR BUSINESS.

### PRELIMINARY SPECIFICATIONS

RANGES	Hino XL Series Straight Truck	
Total GVWR Range lbs. (kg.)	33k - 62k	(15k - 28k)
Front Axle GAWR Range lbs. (kg.)	12k - 16k	(5.5k - 7k)
Rear Axle GAWR Range lbs. (kg.)	21k - 46k	(9.5k - 21k)
Wheelbase Range in. (mm)	217 - 298	(5511 - 7569)
Rear Axle Gear Ratios	4.30 - 4.88	
Frame Yield Strength	120k psi	

TECHNICAL		4x2	6x4
Engine Model	Hino A09	S	S
Engine Horsepower	300 HP	S	S
	360 HP	-	O
Transmission	Allison 3000RDS	S	S
	Allison 3000HS	O	O
	Eaton FAO-14810C	O	O
Fuel Tanks ltr. (US Gallon)	189L (50 Gallon)	S	S
	340L (90 Gallon)	O	O
	454L (120 Gallon)	O	O
	302L+302L (80+80 Gallon)	O	O
DEF Tank	28L (7.4 Gallon)	S	S

TECHNICAL		4x2	6x4
Frame	9mm (0.35") Single	S	-
	11mm (0.433") Single	O	S
	9mm + 5mm (0.35" + 0.19") Reinforced	-	O
Front Spring	Tapered Leaf	S	S
Rear Spring	Multi-Leaf	S	S
	Hendrickson Comfort Air	O	O
	Single Load Leveling with Dump Valve	S	S
	Dual Load Leveling with Dump Valve	O	O
ABS	WABCO 4S/4M	S	-
	WABCO 6S/6M	-	S
Electronic Stability Control	WABCO	S	S
Collision Mitigation System	WABCO OnGuard-Avert	O	O
Lane Departure Warning	WABCO OnLane 2	O	O
Front & Rear Brakes	Bendix S-cam Drum	S	S
	Bendix Disc	O	O
Wheel Size (in.)	Steel 22.5" Powder Coat	S	S
	Aluminum 22.5" Alcoa	O	O

**DISCLAIMER:** All specifications of the products are preliminary. HINO MOTORS CANADA, LTD reserves the right to discontinue items, or make changes at any time, without notice, to equipment, specifications, or materials.

